



AUTOMATIC HOSE REELS VARNISHED FIXED FOR OIL 160 bar

Equipped with:

- Synthetic black rubber hoses 1SC
- Galvanized connections
- Swivelling joint 90° galvanized
- Polyurethane seals



F-400

| Article | Hose length | Ø hose | Inlet-outlet |
|--------------|--------------|--------|-----------------|
| 070-1206-400 | Without hose | - | M1/2"G - M1/2"G |
| 070-1206-310 | 10 m | 3/8" | M1/2"G - M1/2"G |
| 070-1206-410 | 10 m | 1/2" | M1/2"G - M1/2"G |



F-460

| Article | Hose length | Ø hose | Inlet-outlet |
|--------------|--------------|--------|-----------------|
| 070-1306-400 | Without hose | - | M1/2"G - M1/2"G |
| 070-1306-315 | 15 m | 3/8" | M1/2"G - M1/2"G |
| 070-1306-415 | 15 m | 1/2" | M1/2"G - M1/2"G |
| 070-1306-418 | 18 m | 1/2" | M1/2"G - M1/2"G |



F-550

| Article | Hose length | Ø hose | Inlet-outlet |
|--------------|--------------|--------|-----------------|
| 070-1406-400 | Without hose | - | M1/2"G - M1/2"G |
| 070-1406-420 | 20 m | 1/2" | M1/2"G - M1/2"G |
| 070-1406-425 | 25 m | 1/2" | M1/2"G - M1/2"G |



F-555

| Article | Hose length | Ø hose | Inlet-outlet |
|--------------|--------------|--------|-----------------|
| 070-1506-400 | Without hose | - | M1/2"G - M1/2"G |
| 070-1506-500 | Without hose | - | M3/4"G - M3/4"G |
| 070-1506-600 | Without hose | - | M1"G - M1"G |
| 070-1506-430 | 30 m | 1/2" | M1/2"G - M1/2"G |
| 070-1506-515 | 15 m | 3/4" | M3/4"G - M3/4"G |
| 070-1506-520 | 20 m | 3/4" | M3/4"G - M3/4"G |
| 070-1506-615 | 15 m | 1" | M1"G - M1"G |



F-560

| Article | Hose length | Ø hose | Inlet-outlet |
|--------------|--------------|--------|-----------------|
| 070-1606-500 | Without hose | - | M3/4"G - M3/4"G |
| 070-1606-600 | Without hose | - | M1"G - M1"G |
| 070-1606-525 | 25 m | 3/4" | M3/4"G - M3/4"G |
| 070-1606-530 | 30 m | 3/4" | M3/4"G - M3/4"G |
| 070-1606-620 | 20 m | 1" | M1"G - M1"G |
| 070-1606-630 | 30 m | 1" | M1"G - M1"G |

OVERALL DIMENSIONS FIXED

| Mod. | A | B | C | D | E | F | G | H | | | |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-------------|-------|---|
| F-400 | 158 | 120 | 168 | 192 | 95 | 450 | 400 | 435 | 12,50<19,50 | 0,046 | 1 |
| F-460 | 158 | 120 | 168 | 192 | 95 | 480 | 460 | 500 | 16,50<23,00 | 0,060 | 1 |
| F-550 | 200 | 150 | 225 | 270 | 120 | 590 | 550 | 600 | 22,00<45,00 | 0,085 | 1 |
| F-555 | 250 | 200 | 225 | 270 | 170 | 590 | 550 | 600 | 26,00<53,00 | 0,100 | 1 |
| F-560 | 440 | 390 | 225 | 270 | 360 | 590 | 550 | 600 | 33,00<83,00 | 0,180 | 1 |

